



水平安装

墙面安装

负载 (kg)		
力臂及方向 (mm)		A B C
安装方式		水平□ 墙面□
位置重复定位精度		±0.04
皮带(mm)		50
导程(mm)		40
最高速度 (mm/s)		2000
最大可搬重量	水平使用 (Kg)	85
	垂直使用 (Kg)	/
标准行程 (mm)		100-3050mm/50pitch
马达品牌	P:松下□ A:三协□ T:台达□ M:三菱□	
	Y:安川□ H:禾川、汇川□	
功率	伺服: 400W□	伺服: 750W□
	传感器: 外置 ST-303N	
		C1: 1PCS□ C2: 2PCS□
		C3: 3PCS□ C5: 无□
Q:配气嘴□		不配气嘴: 无□
E:经济款□		S:定制款□

系列	VCB220-电机右上折 (RU)		
名称	皮带模组	版本	A/0
型号		页次	/

行程	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000	1050	1100	1150	1200	1250	1300	1350	1400	1450	1500	1550	
L	653	703	753	803	853	903	953	1003	1053	1103	1153	1203	1253	1303	1353	1403	1453	1503	1553	1603	1653	1703	1753	1803	1853	1903	1953	2003	2053	2103	
A	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	
M	1	1	2	2	2	2	3	3	3	3	4	4	4	4	5	5	5	5	6	6	6	6	7	7	7	7	8	8	8	8	
N	6	6	8	8	8	8	10	10	10	10	12	12	12	12	14	14	14	14	16	16	16	16	18	18	18	18	20	20	20	20	
KG	33	34.2	35.4	36.6	37.8	39	40.2	41.4	42.6	43.8	45	46.2	47.4	48.6	49.8	51	52.2	53.4	54.6	55.8	57	58.2	59.4	60.6	61.8	63	64.2	65.4	66.6	67.8	
客户确认																															
行程	1600	1650	1700	1750	1800	1850	1900	1950	2000	2050	2100	2150	2200	2250	2300	2350	2400	2450	2500	2550	2600	2650	2700	2750	2800	2850	2900	2950	3000	3050	
L	2153	2203	2253	2303	2353	2403	2453	2503	2553	2603	2653	2703	2753	2803	2853	2903	2953	3003	3053	3103	3153	3203	3253	3303	3353	3403	3453	3503	3553	3603	
A	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	
M	9	9	9	9	10	10	10	10	11	11	11	11	12	12	12	12	13	13	13	13	14	14	14	14	15	15	15	15	16	16	
N	22	22	22	22	24	24	24	24	26	26	26	26	28	28	28	28	30	30	30	30	32	32	32	32	34	34	34	34	36	36	
KG	69	70.2	71.4	72.6	73.8	75	76.2	77.4	78.6	79.8	81	82.2	83.4	84.6	85.8	87	88.2	89.4	90.6	91.8	93	94.2	95.4	96.6	97.8	99	100.2	101.4	102.6	103.8	
客户确认																															

一般公差		材質		數量/組	1
尺寸範圍	容許差	單位	MM	比例	1:10
1~4	±0.05	核准		日/月/年	
4~16	±0.07				
16~63	±0.1				
63~250	±0.2	設計		日/月/年	
250~1000	±0.3	製圖	邓晓明	日/月/年	
1000~1500	±0.5				

客户名称	
客户签字	