



行程	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000	1050	1100	1150	1200	1250	1300	1350	1400	1450	1500	1550
L	461	511	561	611	661	711	761	811	861	911	961	1011	1061	1111	1161	1211	1261	1311	1361	1411	1461	1511	1561	1611	1661	1711	1761	1811	1861	1911
A	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100
M	1	1	1	2	2	2	2	2	3	3	3	3	4	4	4	4	5	5	5	5	6	6	6	6	6	7	7	7	8	8
N	6	6	6	6	8	8	8	8	10	10	10	10	12	12	12	12	14	14	14	14	16	16	16	16	16	18	18	18	20	20
KG	8.5	9	9.5	10	10.5	11	11.4	12	12.4	13	13.4	13.9	14.4	14.9	15.4	15.9	16.4	16.9	17.3	17.9	18.5	19.1	19.7	19.7	21.5	22.1	22.7	23.3	23.9	
客户确认																														
行程	1600	1650	1700	1750	1800	1850	1900	1950	2000	2050	2100	2150	2200	2250	2300	2350	2400	2450	2500	2550	2600	2650	2700	2750	2800	2850	2900	2950	3000	3050
L	1961	2011	2061	2111	2161	2211	2261	2311	2361	2411	2461	2511	2561	2611	2661	2711	2761	2811	2861	2911	2961	3011	3061	3111	3161	3211	3261	3311	3361	3411
A	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200
M	8	8	9	9	9	9	10	10	10	10	11	11	11	11	12	12	12	12	13	13	13	13	14	14	14	14	15	15	15	15
N	20	20	22	22	22	22	24	24	24	24	26	26	26	26	28	28	28	28	30	30	30	30	32	32	32	32	34	34	34	34
KG	24.5	25.1	25.7	26.3	26.9	27.5	28.1	28.7	29.3	29.9	30.5	31.1	31.7	32.3	32.9	33.5	34.1	34.7	35.3	35.9	36.5	37.1	37.7	38.3	38.9	39.5	40.1	40.7	41.3	41.9
客户确认																														



水平安装		墙面安装	
负载 (kg)			
力臂及方向 (mm)	A	B	C
安装方式	水平	□	墙面
位置重复定位精度	±0.04		
皮带 (mm)	25		
导程 (mm)	40		
最高速度 (mm/s)	2000		
最大可搬重量	水平使用 (Kg)	25	
	垂直使用 (Kg)	/	
标准行程 (mm)	100-3050mm/50pitch		
马达品牌	P:松下 □ V:安川 □	A:三协 □ H:禾川 □	T:台达 □ J:汇川 □
功率	伺服: 200W □	伺服: 400W □	
传感器: 外置 ST-303N	C1: 1PCS □	C2: 2PCS □	C3: 3PCS □
E经济款 □	S:定制款 □		
系列	VTB135-电机左下折 (LD)		
名称	皮带模组		
型号			
一般公差	材质	数量	组
尺寸范围	容许差	MM	1
1~4	±0.05		
4~16	±0.07		
16~63	±0.1		
63~250	±0.2		
250~1000	±0.3		
1000~1500	±0.5		
客户名称	製圖	邓晓明	日/月/年
客户签字			