



行程	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000	1050	1100	1150	1200	1250	1300	1350	1400	1450	1500	1550
L	587	637	687	737	787	837	887	937	987	1037	1087	1137	1187	1237	1287	1337	1387	1437	1487	1537	1587	1637	1687	1737	1787	1837	1887	1937	1987	2037
A	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150
M	1	1	1	2	2	2	2	3	3	3	3	4	4	4	4	5	5	5	5	6	6	6	6	7	7	7	7	8	8	8
N	6	6	6	8	8	8	8	10	10	10	10	12	12	12	14	14	14	14	14	16	16	16	18	18	18	18	20	20	20	20
KG	28.8	30	31.2	32.4	34.8	36	37.2	38.4	39.6	40.8	42	43.2	44.4	45.6	46.8	48	49.2	50.4	51.6	52.8	54	55.2	56.4	59.2	59.8	60	61.2	62.4	63.6	64.8
行程	1600	1650	1700	1750	1800	1850	1900	1950	2000	2050	2100	2150	2200	2250	2300	2350	2400	2450	2500	2550	2600	2650	2700	2750	2800	2850	2900	2950	3000	3050
L	2087	2137	2187	2237	2287	2337	2387	2437	2487	2537	2587	2637	2687	2737	2787	2837	2887	2937	2987	3037	3087	3137	3187	3237	3287	3337	3387	3437	3487	3537
A	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50
M	8	9	9	9	9	10	10	10	10	11	11	11	11	12	12	12	13	13	13	13	14	14	14	14	15	15	15	15	16	16
N	20	22	22	22	22	24	24	24	24	26	26	26	26	28	28	28	30	30	30	30	32	32	32	32	34	34	34	34	36	36
KG	66	67.2	68.4	69.6	70.8	72	73.2	74.4	75.6	76.8	78	79.2	80.4	81.6	82.8	84	85.2	86.4	87.6	88.8	90	91.2	92.4	93.6	94.8	96	97.2	98.4	99.6	100.8



水平安装

墙面安装

负载 (kg)	A B C		
力臂及方向 (mm)	A B C		
安装方式	水平 □ 墙面 □		
位置重复定位精度	±0.04		
皮带(mm)	50		
导程(mm)	40		
最高速度 (mm/s)	2000		
最大可搬重量	水平使用 (Kg)	85	
	垂直使用 (Kg)	/	
标准行程 (mm)	100-3050mm/50pitch		
马达品牌	P:松下 □ V:安川 □	A:三协 □ H:禾川、汇川 □	T:台达 □ M:三菱 □
功率	伺服: 400W □	伺服: 750W □	
传感器: 外置 ST-303N	C1: 1PCS □ C2: 2PCS □	C3: 3PCS □ C5: 无 □	
E:经济款 □	S:定制款 □		
系列	VTB220-电机左下折 (LD)		
名称	皮带模组		
型号		版次	A/0
一般公差		数量/组	1
尺寸範圍	容許差	材質	單位
1~4	±0.05		MM
4~16	±0.07	核准	比例
16~63	±0.1	設計	日/月/年
63~250	±0.2	設計	日/月/年
250~1000	±0.3	製圖	日/月/年
1000~1500	±0.5	鄧曉明	
客户名称			
客户签字			