



行程	100	150	200	250	300	350	400	450	500	550	600	650	700	750	800	850	900	950	1000	1050	1100	1150	1200	1250	1300	1350	1400	1450	1500	1550
L	587	637	687	737	787	837	887	937	987	1037	1087	1137	1187	1237	1287	1337	1387	1437	1487	1537	1587	1637	1687	1737	1787	1837	1887	1937	1987	2037
A	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150
M	1	1	1	2	2	2	2	2	3	3	3	4	4	4	4	5	5	5	5	5	6	6	6	7	7	7	7	8	8	8
N	6	6	6	8	8	8	8	8	10	10	10	12	12	12	14	14	14	14	14	16	16	16	18	18	18	18	18	20	20	20
KG	28.8	30	31.2	32.4	34.8	36	37.2	38.4	39.6	40.8	42	43.2	44.4	45.6	46.8	48	49.2	50.4	51.6	52.8	54	55.2	56.4	59.2	59.8	60	61.2	62.4	63.6	64.8
客户确认																														
行程	1600	1650	1700	1750	1800	1850	1900	1950	2000	2050	2100	2150	2200	2250	2300	2350	2400	2450	2500	2550	2600	2650	2700	2750	2800	2850	2900	2950	3000	3050
L	2087	2137	2187	2237	2287	2337	2387	2437	2487	2537	2587	2637	2687	2737	2787	2837	2887	2937	2987	3037	3087	3137	3187	3237	3287	3337	3387	3437	3487	3537
A	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50	100	150	200	50
M	8	9	9	9	9	10	10	10	10	11	11	11	11	12	12	12	13	13	13	13	13	14	14	14	14	14	15	15	15	16
N	20	22	22	22	22	24	24	24	24	26	26	26	26	28	28	28	30	30	30	30	30	32	32	32	32	34	34	34	34	36
KG	66	67.2	68.4	69.6	70.8	72	73.2	74.4	75.6	76.8	78	79.2	80.4	81.6	82.8	84	85.2	86.4	87.6	88.8	90	91.2	92.4	93.6	94.8	96	97.2	98.4	99.6	100.8



水平安装



墙面安装

负载 (kg)	A B C	
力臂及方向 (mm)	A B C	
安装方式	水平 □ 墙面 □	
位置重复定位精度	±0.04	
皮带(mm)	50	
导程(mm)	40	
最高速度 (mm/s)	2000	
最大可搬重量	水平使用 (Kg)	85
	垂直使用 (Kg)	/
标准行程 (mm)	100-3050mm/50pitch	
马达品牌	P:松下 □ Y:安川 □	A:三协 □ H:禾川、汇川 □
功率	伺服: 400W □	伺服: 750W □
传感器: 外置 ST-303N	C1: 1PCS □ C2: 2PCS □	C3: 3PCS □ C5: 无 □
E:经济款 □	S:定制款 □	
系列	VTB220-电机台下折 (RD)	
名称	皮带模组	
型号		
一般公差		
尺寸範圍	容許差	單位
1~4	±0.05	MM
4~16	±0.07	核准
16~63	±0.1	設計
63~250	±0.2	設計
250~1000	±0.3	製圖
1000~1500	±0.5	鄧曉明
客户名称		
客户签字		